



TAPMATIC[®] DUAL ACTION PLUS #2

CUTTING FLUID



FEATURES

- Provides superior lubricity in machining aluminum and its alloys
- Reduces friction
- Eliminates chip welding
- Improves surface finish
- Extends tool life

APPLICATIONS

- Boring
- Broaching
- Drawing
- Drilling
- Engraving
- Facing
- Finishing
- Grinding
- Reaming
- Sawing
- Stamping
- Tapping
- Threading
- Turning
- Milling



PACKAGES

Net Content	Part No.
16 fl. oz. (0.473 liters)	40220
1 gal. (3.78 liters)	40230
55 gal. (208 liters)	40260

PROPERTIES

Color:	Medium Amber	Specific Gravity (Water=1):	0.83-0.85 @ 68°F (20°C)
Odor:	Mild Fatty	VOC content:	73%, 613 g/L (per E.P.A. definitions)
Flash Point (TCC):	158°F (70°C) minimum	Viscosity:	<7 mm ² /second @ 77°F(25°C)
Boiling Point:	383°F (195°C) @ 101 KPA		

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE : WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2010 LPS Laboratories • LPS[®] is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2178• Rev. 5/2010