



THERMAPLEX[®] MULTI-PURPOSE

BEARING GREASE



FEATURES

- Ideal for lubricating all types of bearings
- Extends relubrication periods
- Prolongs bearing life
- Excellent load carrying properties
- Good corrosion resistance
- Reduces grease consumption
- “Product of the Year” winner for Lubricants World Magazine



PACKAGES

Net Fill

- 14.1 oz. (400 grams) cartridge
- 35 lbs. (5 gallons) pail
- 120 lbs. (16 gallons) keg
- 400 lbs. (55 gallons) drum

Part No.

- 70614
- 70606
- 70635
- 70655

APPLICATIONS

- Cement Mixers
- Elevators
- Motors
- Ventilator Fans
- Conveyors
- Gas Extractors
- Tray Loaders

PROPERTIES

4-Ball Weld Load:
>600 kg

Appearance/Physical State:
Creamy Paste

Base Oil Viscosity:
850 SUS @ 100°F
180 cst. @ 40°C
17 cst. @ 100°C

Color:
Blue

Copper Corrosion
1A/1B

Dropping Point:
429°F (220°C)

Flash Point:
>392°F (~200°C) PMCC

NLGI Grade:
2

Odor:
Petroleum

Specific Gravity (water=1):
1.00

Temperature Range:
-22°F (-30°C) to 350°F (177°C)

Thickener Type:
Lithium Complex

Timkin “OK” Load:
50 lbs.

Vapor Density (air=1):
>1

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE: WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

4647 Hugh Howell Road • Tucker, GA 30084 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2012 LPS Laboratories • LPS[®] and ThermaPlex[®] are registered trademarks of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2155 • Rev. 6/2012